



Model	GTJZ0808
PRODUCTIVITY	
Max. platform height	8.10 M
Max. working height	10.10 M
Extension outreach	0.90 M
Turning radius (outside)	2.10 M
Turning radius (inside)	0 M
Rising / falling speed (without loading)	30-35 s / 35-40 s
Grade ability	25 %
Load Capacity (platform)	250 kg
Driving speed (stowed)	0~3.20 km/h
Driving speed (raised)	0~0.8km/h
Max allowable wind speed indoor	0 m/s
Max allowable wind speed outdoor	-
Max allowable slope (front/back)	3 °
Max allowable slope (side/side)	1.5 °
Max allowable occupants indoor	2 p
Max allowable occupants outdoor	-
Max allowable side force indoor	400 N
Max allowable side force outdoor	-
DIMENSIONS	
Overall length (stowed)	2.39 m
Overall width (stowed)	0.81 m
Overall height (stowed, guardrail folded)	1.96 m
Overall height (stowed, guardrail unfolded)	2.35 m
Ground clearance	0.10 m
Wheelbase	1.85 m
Platform size (L x W x H)	2.25 x 0.81 x 1.10 m
Overall weight	1920 kg
Tire	380 x 125 mm / solid
Hydraulic oil tank vol.	14 l
Hydraulic system vol.	18 l
Battery	6V*4/225 AH
Control voltage	24 VDC
Power unit	24 VDC, 3 KW
Drive & steer model	2 WD, front wheel
Input voltage of charger	100~240V AC
Output current of charger	25 A
Hydraulic system pressure	24 MPA
Brake	2 rear wheel

VDS. NV

NIEUWE STEENWEG 25 - 9810 EKE-NAZARETH
TEL 09 385 37 45 - FAX 09 385 37 44

INFO@NVVDS.BE
WWW.NVVDS.BE

BTW BE 0449.061.401
RPR OUDENAARDE

KBCIBAN BE08447061206113
BIC KREDBEBB