



V.D.S. NV

Model	GTJZ0608
Dimensions	
A Platform height max.	21 ft (6.3 m)
Working height max.	27 ft (8.3 m)
B Platform extended	3 ft (0.9 m)
C Length - stowed	7 ft 8 in (2.39 m)
Width - stowed	2 ft 7 in (0.81 m)
D Height - folding guardrails	7 ft 3 in (2.22 m)
Height - rails folded	6 ft (1.83 m)
Height - fixed rails	7 ft 3 in (2.22 m)
E Wheelbase	6 ft (1.85 m)
Ground clearance	3 in (0.1 m)
Platform size (L*W*H)	7 ft 4 in*2 ft 7 in*3 ft 6 in (2.25 m*0.81 m*1.1 m)
Productivity	
Max. platform occupancy	2 (indoor) 1 (outdoor)
Lift capacity	838 lbs (380 kg)
Lift capacity - extension deck	265 lbs (120 kg)
Drive speed - stowed	0~2.0 mph (0~3.2 km/h)
Drive speed - raised	0~0.5 mph (0~0.8 km/h)
Gradeability	30%
Turning radius - inside	0 ft (0 m)
Turning radius - outside	6 ft 9 in (2.1 m)
Raise / Lower speed	27/33 s
Controls	Proportional
Drives	Dual front wheel
Brakes	Dual rear wheel
Tire size (solid non-marking)	15 in * 5 in (380 mm * 125 mm)

Nieuwe Steenweg 25
T 09 385 37 45

9810 EKE NAZARETH
F 09 385 37 44

info@nvvds.be
www.nvvds.be



V.D.S. NV

Power

Power source 24V DC (4*6V, 225Ah batteries)

Hydraulic system capacity 4.76 gal (18 L)

Power 3 KW

Weight

Indoor & outdoor general 1830 kg

Standards Compliance CE/ ISO/ ADR/ ARAMCO



Nieuwe Steenweg 25
T 09 385 37 45

9810 EKE NAZARETH
F 09 385 37 44

info@nvvds.be
www.nvvds.be