



Model	GTJZ1012 / GN 3246
PRODUCTIVITY	
Max. platform height	10 M
Max. working height	12 M
Extension outreach	0.90 M
Turning radius (outside)	2.35 M
Turning radius (inside)	0 M
Rising / falling speed (without loading)	55 s / 40 s
Grade ability	25 %
Load Capacity (platform)	320 kg
Driving speed (stowed)	0~3.2km/h
Driving speed (raised)	0~0.8km/h
Max allowable wind speed indoor	-
Max allowable wind speed outdoor	12.5 m/s
Max allowable slope (front/back)	3 °
Max allowable slope (side/side)	1.5 °
Max platform occupants indoor	2
Max platform occupants outdoor	1
Max allowable side force indoor	400 N
Max allowable sideforce outdoor	200 N
DIMENSIONS	
Overall length (stowed)	2.43 m
Overall width (stowed)	1.15 m
Overall height (stowed, guardrail folded)	1.92 m
Overall height (stowed, guardrail unfolded)	2.58 m
Ground clearance	0.09 m
Wheelbase	1.87 m
Platform size (L x W x H)	2.30 x 1.15 x 1.10 m
Overall weight	2650 kg
Tire	406 x 125 mm / solid
Hydraulic oil tank vol.	23 l
Hydraulic system vol.	30 l
Battery	6V*4/225 AH
Control voltage	24 VDC
Power unit	24 VDC, 3 KW
Drive & steer model	2 WD, front wheel
Input voltage of charger	100~240V AC
Output current of charger	25 A
Hydraulic system pressure	24 MPA
Brake	2 rear wheel

